



REV	DESCRIPTION	DATE
△	RDC-99113	黄智宏 2010/03/12
△	RDK-100045	陳必偉 2011/06/20
△	RDCM-107003	郭碧紋 2018/01/19
△	RDCM-107141	林淑禎 2018/11/12
△	RDCM-108002	楊駿為 2019/04/19

- NOTE :
1. OPERATING TEMPERATURE RANGE : -20°C~+125°C
  2. MAXIMUM ELECTRICAL RATING : 600 VOLTS MAX.
  3. HOUSING ELECTRICAL : POLYCARBONATE(PC)
  4. SPRING MATERIAL : STAINLESS STEEL
  - △5. COLOR : GREY
  - △6. TRY TO AVOID OIL OR CHEMICAL EXPOSURE WHEN USING THE CONNECTORS.

Tolerance Unless Otherwise Specified	
0 > 6 mm	±0.20 ANGLE
6 > 18 mm	±0.30 0° REF ±
18 > 30 mm	±0.40 ° ±
30 > 75 mm	±0.50 ° ±

NAME	2POS. HOUSINGS 50Amp HOUSINGS			UNIT	mm
PART NO.	BMC2S-GREY	MATERIAL	PC	APPROVE	黃智宏
NUMBER	KA-93047-C	SCALE	REV. SHEET	CHECKED	劉建強
DATE	2007/05/31	1/1	1-5 10F1	DRAWN	黃智宏

**KST. K.S. TERMINALS INC.**